

Hot Sale [Fiber Cement Wall Board](#) For Interior Walls



Fiber Cement Wall Board Specification:		
Thickness(mm)	Width(mm)	Length(mm)
5--25	1220	2440, 3000
Dimensional deviation:		
Thickness	≤8mm	±0.3mm
	8--12mm	±0.5mm
	≥12mm	±0.8mm
Width	≤1220mm	±3mm
	>1220mm	±4mm
Length	≤2440mm	±5mm
	>2440mm	±8mm
Physical properties:		
Density	1.2-1.6g/cm ³	
Thermal conductivity	≤0.29 W/(m.k)	
Water absorption	≤28%	
Water contain	≤10%	
Moisture movement	≤0.25%	
Bending strength	oven dry	≥16 Mpa
	saturation with water	≥13 Mpa
Non-combustibility	class A	

Fiber cement board can be used for exterior wall cladding,interior (toilet) partition,sound absorption ceiling,curtain wall scale board,composite wall panel,outdoor billboard,thermal baffle,floor tiles of office building,hotel,hospital,factory building,school,villa,theatre and other kinds of art building.

Packing & Loading



FAQ

1. Are you manufacturer or trade Company?

We are manufacturer that have 2 imported production lines, yearly capacity can be 20 million square meters.

2. Which is the loading port?

Qingdao, Tianjin, Shanghai or any other China port you need. If provided destination port, CFR and CIF can be quoted for your reference.

3. What's your Minimum order quantity(MOQ) of your product?

1x20"GP, small orders can be negotiated.

4. What terms of payment you usually use?

T/T 50% deposit and 50% should paid out before shipment. LC payment terms are negotiable if large order.

5. What is your lead time for your goods?

About 10-15 days

6. How do you guarantee the quality of your product?

We have strict QC inspection in each process. There are test reports for our products. All our products meet industry standards.

7. Do you accept OEM?

Yes, we can print your logo or information on the products or packing.

Welcome to visit our factory to view more details.