



Detail		
Floor	Steel frame	made from cold rolled, welded steel profiles, 4 mm thick
		4 corner casts, welded
		2 fork lift pockets (except 30') - distance 1200mm
		(internal clearance of fork lift pockets: 240×80 mm)
		steel cross members, thickness=2mm
	Insulation	100 mm thick Rock Wool
	Subfloor	0.5mm thick, galvanized steel sheet
	Floor	8mm plywood board
		1.8mm PVC floor
		flammability class B1 - hardly combustible
		smoke density class Q1 - low smoke emission
		wear resistance factor: T level
Roof	Steel frame	made from cold rolled, welded steel profiles, 3mm thick
		4 corner casts, welded
		steel cross members, thickness=2mm
	Roof cover	0.5mm thick, galvanized steel sheet 360 degree seaming at joint of roof panels
	Insulation	100 mm thick Rock Wool
	Ceiling	10 mm chipboard (V 20), laminated on both sides, white the chipboard complies with the emission value E1
	CEE connector	sunken in frame on short end side
Insulation	Rockwool	density:120kg/m3
		flammability class A- non combustible
		certificated: CE & GL
	EPS	density:10kg/m3
		flammability class B1- non combustible
		smoke density class Q1 - low smoke emission
		certificated: CE & GL