



## Detail

		made from cold rolled, welded steel profiles, 4 mm thick
		4 corner casts, welded
	Steel frame	2 fork lift pockets (except 30') - distance 1200mm (internal clearance of fork lift pockets: 240×80 mm)
		steel cross members, thickness=2mm
<b>Floor</b>	Insulation	100 mm thick Rock Wool
	Subfloor	0.5mm thick, galvanized steel sheet
		8mm plywood board
		1.8mm PVC floor
	Floor	flammability class B1 - hardly combustible smoke density class Q1 - low smoke emission wear resistance factor: T level

		made from cold rolled, welded steel profiles, 3mm thick
	Steel frame	4 corner casts, welded steel cross members, thickness=2mm
<b>Roof</b>	Roof cover	0.5mm thick, galvanized steel sheet 360 degree seaming at joint of roof panels
	Insulation	100 mm thick Rock Wool
	Ceiling	10 mm chipboard (V 20), laminated on both sides, white the chipboard complies with the emission value E1
	CEE connector	sunken in frame on short end side density:120kg/m3
	Rockwool	flammability class A- non combustible certificated: CE & GL density:10kg/m3
<b>Insulation</b>	EPS	flammability class B1- non combustible smoke density class Q1 - low smoke emission certificated: CE & GL