





| Sort                      | Name                                | Specification  |
|---------------------------|-------------------------------------|--|
|                           | 20'GP                               | Length:6055mm Width:2438m Height:2591mm<br>Weight:2145KGS  |
| <b>Specification</b>      | 40'GP                               | Length:12192mm Width:2438mm Height:2591mm<br>Weight:3650KGS  |
|                           | 40'HQ                               | Length:12192mm Width:2438mm Height:2896mm<br>Weight:3800KGS  |
|                           | Wall                                | Material: steel  |
|                           | Roof                                | Material: steel  |
|                           | Door                                | Aluminium alloy, wood ,steel or customers'<br>requirement  |
|                           | Window                              | Aluminium alloy, wood or customers' requirement  |
| <b>Standard accessory</b> | Decorative floor                    | PVC or laminated flooring in living area and aluminium<br>panel in bathroom and kitchen or customers'<br>requirement |
|                           | Water supply and<br>Drainage system | Provided plan, design and construction or customers'<br>requirement  |
|                           | Electric system                     | Provided plan, design and construction or customers'<br>requirement  |

|                                |                       |               |
|--------------------------------|-----------------------|---------------|
| <b>Technical<br/>parameter</b> | Resistant temperature | -50°C to 70°C |
|                                | Fire proof            | B2 grade      |
|                                | Earthquake resistance | 8Grade        |
|                                | Wind resistant        | 120km/h       |